

Spreading or Short Chop

You can choice !

Change from short chop to just spreading at the flick of a switch

TX 27 XL Polycut

Mounted or trailed - Latéral chute or Universal Chute - Capacity : 2.3 m³ Straw spreading up to 15 meters

Universal chute model



Stainless steel housing

Powerdrive system: An innovative process developing maximum power for the separator (+ 120 CV) both quieter and more comfortable.

Advantages :

- Up to 120 CV power available to the separator
- Starting separated from the rotor and the separator
- Allows 100% use of the body shell volume
- Progressive clutch control of the separator

Lateral chute model



Controls electric wire

2 Speed Gaer Box



Duel flow Turbine and 8 Blades « Twin »

At the heart of the machine, its high performance ensures both regular straw distribution over a wide area and quick and even silage distribution. Powerful but quiet : The 8 blades and their 3 bearing points on the rotor wheel are exceptionally strong and perfectly balanced.

Trailed model



Self Loading provided by hydraulic rear tailgate moved by 2 hydraulic rams

320° Swivel chute (option)

Interchangeable sieve 30 , 60 or 90 mm

Cubicles, Henhouses, Nutrition



Henhouses, Nutrition



Cubicles



The sieve



Short wisp

Straw is cut by a system of blades and rotating lingers until it is short enough to pass through a screen

Stalling, mulch Areas



Long wisp

Spread straw: the knives are taken out off opération hydraulically, allowing the straw to be teased out of the bale and straight into the discharge rotor



Round bales ø until 2 m and Handles rectangular bales L: 2.50 m

Options :

- 320 Directional chute (only for POLYFLOW)
- Extra for second Electric Control (door + conveyor)
- Hydraulic flow divider (more than 50 l / mn)
- Sieve calibration 30 mm
- Sieve calibration 60 mm
- Atomizer



With Atomizer option